



I Direction		
PIN	Signal	Insulation Color Overall Shield
1	Overall Shield	
2		
3	Y + Receive	BLUE
4	Y Transmit	BLUE
5	Y - Receive	BLACK
6	Y Ground	YELLOW
7	Shield	
8	X Ground	GREEN
9	X+Receive	WHITE
10	X Transmit	RED
11	X-Receive	RED
12		

sensor 1	Y-Transmit
sensor 2	Y-Receive
sensor 3	X-Receive
sensor 4	X-Transmit

Unmarked Tolerance		
from (mm)	to (mm)	Quality Level Level
0	10	±0.05
10	50	±0.10
50	100	±0.15
100	200	±0.20



A.u.S. Spielgeräte GesmbH
 Scheydgasse 48 A-1210 Wien
 Tel. +43-1-271 66 00 Fax: +43-1-271 66 00 75
 E-mail: verkauf@aus.at
 http://www.aus.at
 Öffnungszeiten: Mo-Fr. 9-18 Uhr

SAW screen specs		
mark	Content of Amendment	Edition
Design		standard
Drawing		process
Check		Approve
Author		Date
sign	weight	Scale
AD		Free
Total X1P X1P		

product	6783
Drawing No.	

Product Requirement:
 Glue line way: on the bevel edge