

Terminal
CON1Housing
Leotronics 6740-1160
(2x8way 4.2mm pitch with latch, 6A de-rated)Crimp
6744-2000
(tin plated, female)

Connectivity by conductor

CON1	Gauge	Colour	Comments					
Pin	(AWG)							
16	22	White	SSP TXD (Vend1)					
14	22	Blue	SSP RXD (Inhibit1)					
9	22	Red	V IN					
1	22	Black	GND					

Note:

Pins 8 is loaded with crimp but not connected All other pins are unloaded



A.u.S. Spielgeräte GesmbH Scheydgasse 48 A-1210 Wien el. +43-1-271 66 00 Fax.+43-1-271 66 00 75 E-mail: verkauf@aus.at http://www.aus.at Öffnungszeiten: Mo-Fr. 9-18 Uhr

-		•			All parts must be rated to at least UL94-VW1 All connector housings must be rated to UL94-V0						Sma	Smart Payout to Host (6A rated connector)						-		FINISH -	
3	2		-	_			1		NOT	TO SCALE		- Custo	omer pr	oposal (power	only)					
В	1	09/09/09							1,000,000	dimensions	DRAWN B	Y		DATE	CHE	CKED BY		DATE		TOOL NO.	
ISSUE NO.	MOD NO.	DATE	MOD BY				3rd A	NGLE PROJECTION.	in mm ±2mm								·				
A	В	C	D E	F	G	Н	1 1	J	К	L	M	N	0	P	Q	R	S	T	U	V	W